
# **Filter Housings**

## 10" and 20" Standard Filter Housings

SH

Pure Aqua's 10" and 20" standard filter housings are constructed of a durable reinforced polypropylene or clear Styrene-Acrylonitrile (SAN). Pure Aqua's line of standard filter housings are available in many different colors, styles and connections sizes. Pure Aqua's housings will accommodate a wide range of 2-1/2" or 2-5/8" diameter cartridges. The reinforced polypropylene cap offers an optional pressure-relief button on the inlet side to relieve pressure inside the housing when changing filter cartridges.





### **Applications**

- Reverse osmosis pre-filtration
- Reverse osmosis post-filtration
- Food & beverage industry
- UV pre-filtration
- Residential
- Commercial
- Industrial

#### 10" Length (2.5" Diameter)

Part Number	Description	Inlet Size (in)	Outlet Size (in)
H-1034-BL	Blue 10"	3/4"	3/4"
H-1034-CL	Clear 10"	3/4"	3/4"

#### 20" Length (2.5" Diameter)

Part Number	Description	Inlet Size (in)	Outlet Size (in)
H-2034-BL	Blue 20"	3/4"	3/4"
H-2034-CL	Clear 20"	3/4"	3/4"

## **Features & Benefits**

- Easy installation
- Thick walls for increased strength
- Leak-proof seal
- Wide range of connection sizes
- Wide range of colors
- Durable construction

 Material (housing)
 Polypropylene

 Material (cap)
 Reinforced polypropylene

 Material (o-ring)
 Buna-N

 Material (pressure relief)
 300-series stainless steel, EPDM, and polypropylene

 Maximum temperature
 52°C/125°F

 Maximum pressure
 125 psi

NOTE: 10" and 20" standard units are available in white, black, almond, clear, and blue, with 1/4", 3/8", 1/2", 3/4" and 1". Please add PR to the end of a part number for pressure relief option.

**Specifications** 



Water Treatment and Reverse Osmosis Systems

sales@pureaqua.com Tel: +1-714-432-9996 www.pureaqua.com Fax: +1-714-432-9898



Authorized Dealer: